



アングル

SUS304

YOSHU 2014.03

寸法 印は切断可能品	長さ (mm)			辺の許容差	厚さの許容差
	4000	5000	6000		
3 × 20	3.58	4.47	5.36	±1.5	±0.4
3 × 25	4.52	5.65	6.78	±1.5	±0.5
3 × 30	5.48	6.85	8.22	±2.0	±0.5
3 × 40	7.40	9.25	11.1	±2.0	±0.6
3 × 50	9.48	11.8	14.2	±2.0	±0.6
4 × 40	9.64	12.2	14.5	±2.0	±0.6
4 × 50	12.4	15.5	18.5	±2.0	±0.6
5 × 30	8.70		13.1	±2.0	±0.5
5 × 40	11.9	14.9	17.9	±2.0	±0.6
5 × 50	15.3	19.1	22.9	±2.0	±0.6
6 × 30			15.2	±2.0	±0.6
6 × 50	17.9	22.4	26.9	±2.0	±0.6
6 × 60			32.6	±3.0	±0.6
6 × 65	23.9	29.9	35.8	±3.0	±0.6
6 × 75	27.7	34.6	41.5	±3.0	±0.7

(mm)

(kg/本)

(mm)

(mm)



アングル

S U S 3 0 4

YOSHU 2014.03

寸 法 印は切断可能品	長 さ (mm)			辺の許容差	厚さの許容差
	4000	5000	6000		
6 × 100	37.3	46.6	55.9	± 3.0	± 0.7
7 × 70			44.5	± 3.0	± 0.7
8 × 80			57.8	± 3.0	± 0.7
8 × 100	48.8		73.2	± 3.0	± 0.7
9 × 75	40.4	50.5	60.6	± 3.0	± 0.7
9 × 90	49.2		73.8	± 3.0	± 0.7
10 × 100	60.4	75.5	90.6	± 4.0	± 0.8

(mm)

(kg/本)

(mm)

(mm)



直角度 90° ± 2°

曲がり 長さ1mにつき3mm以下とし、全長に対しては、
3mm × 長さ (m) ÷ 1m以下とする。

長さ + 40mm、 - 0